

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

Adresse	<b>Interfloat Corporation</b> Grabenackerweg 3, FL-9491 Ruggell,
Pays	Liechtenstein

## PRODUITS OU MACHINES

**Interfloat Corporation** has been a supplier of the European solar industry since 1982. Delivery reliability, superior glass quality as well as the continuous improvement of our products is the hallmark of the company.

### GMB solar glass | SINA solar glass

The microstructure of GMB solar glass SINA is characterised by specially designed forming rollers on both glass surfaces. The surface of SINA is a non-geometrically aligned structure with a typical roughness height (Rz) of approx. 15 µm (taken from a measuring length of 15 mm). The structure demonstrates a high "density" (number of bumps and holes per unit of length) in order to limit direct reflection and hence reduce dazzling to a minimum. The consistent appearance of the glass is guaranteed in so far as the reflection characteristics of the glass are constantly monitored in our in-house laboratory and corrected as appropriate. GMB solar glass SINA is ideal for both applications – PV modules and thermal collectors.

### GMB solar glass | CONE Solar glass

CONE has two differently structured surfaces. One surface of CONE has a geometric, pyramid formed structure (see diagram). The other surface exhibits the same microstructure as GMB solar glass SINA. In PV modules the pyramidal structure forms the interface to the composite material (e.g. EVA) which encloses the solar cell. The pyramidal structure is no longer visible after lamination into the PV module. In thermal collectors the pyramidal structure is usually oriented towards the absorber. The advantages of the CONE structure are the significant reduction of dazzling effects and the considerably poor view into the inside of the collector. Small shortcomings in the absorption surface (fingerprints, etc.) can therefore be concealed.

### GMB solar glass | ASTRA GMB solar glass

ASTRA has a rough, non-geometric structure similar to SINA on the one side but with a significantly larger roughness height (Rz) of approx. 60 µm (taken from a measuring length of 15 mm). The other surface has a very delicate microstructure. ASTRA glass has a very high angle factor (IAM) and is therefore also ideal for collectors of the highest performance. ASTRA glass offers minimal reflection or dazzling as well as a very poor view into the inside of the collector. As such, small visual blemishes (such as fingerprints) are easily concealed. Various collector manufacturers use ASTRA glass for the purposes of product diversification. Collectors with ASTRA glass are recognisably visually different to a collectors fitted with SINA glass. Of course, GMB solar glass ASTRA can also be implemented in PV modules. The orientation of the rough structure can be, according to the desired visual appearance, towards the inside or outside.

### Company Profile of **Interfloat Corporation**

A service of glasssglobal.com, an affiliate of glasssglobal group.

Les informations publiées sur ce document sont soumises au droit d'auteur et appartiennent à la société en question resp. à la source des adresses. Tous les droits sont réservés expressément. N'importe quel utilisateur qui accède à un tel matériel peut faire ainsi seulement pour sa propre utilisation personnelle, et l'usage d'un tel matériel est au risque unique de l'utilisateur. La redistribution ou toute autre exploitation commerciale des adresses est expressément interdite. Là où une adresse est fournie par un tiers, chaque utilisateur accepte d'observer et être lié par les limites spécifiques de l'utilisation. Glass Global ne représente ou n'approuve pas l'exactitude ou la fiabilité d'aucune des informations citées dans les adresses ou pages externes auxquelles l'on se réfère ici. www.glasssglobal.com - The International Portal to the Glass Industry - OGIS GmbH