

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

Adresse **Sicherheitsglastechnik Oelsnitz (Vogtl.) GmbH**
Talstraße 2
D-08606 Oelsnitz (Vogtl.)

Pays Allemagne

PRODUITS OU MACHINES

Toughened Glass

Toughened safety glass is made via a thermal toughening process. A heating and cooling process distribute the stress in the glass. The glass is heated to a temperature above 620°C, and then air-cooled. This sudden cooling induces tensile stresses in the centre of the glass balanced by compressive stresses in the surface.

If broken, this equilibrium of stresses is destroyed and the glass crumbles into small pieces that have blunt edges. The benefits of toughened safety glass are its increased bending, impact, shock and thermal shock resistance.

As a result of its safety toughened safety glass can be used for exterior and interior applications.

Product Range / Production Options Toughened Glass

- Maximum size 9,000mm x 3,300mm
- Thickness range between 4mm - 19mm
- Edge working
- Mitered edges
- Drilled holes
- Countersunk holes
- Corner cut-outs
- Edge cut-outs
- Centre cut-outs
- Round corners
- Shaped glass
- Fully enamelled glass, screen printing

Heat Strengthened Glass

Heat strengthened glass undergoes a similar manufacturing process as toughened glass. The only difference is the significantly slower cooling process. By cooling the glass at a slower pace less stress is induced in the glass. This results in heat strengthened glass having a similar breakage pattern as float glass. Heat strengthened glass can only be regarded as safety glass when used in laminated glass.

Product Range / Production Options Heat Strengthened Glass

- Maximum size 9,000mm x 3,300mm
- Thickness range between 4mm - 12mm
- Edge working
- Mitered edges
- Drilled holes
- Countersunk holes
- Corner cut-outs
- Edge cut-outs
- Centre cut-outs
- Round corners
- Shaped glass
- Fully enamelled glass, screen printing

Laminated Safety Glass

Laminated safety glass consists of at least two panes of either float glass, toughened glass or heat strengthened glass firmly bonded with viscoelastic, highly tear resistant Polyvinyl Butyral (PVB) interlayers.

In the event of breakage, the glass fragments are retained by the interlayer. The thickness of the interlayer affects the remaining load capacity. The benefits of laminated safety glass are its bending and impact resistance and its ability to resist high temperatures. Depending on the panes, SGT's laminated safety glass has the following benefits:

- protection from glass fallout in overhead glazing
- impact resistance
- intrusion resistance
- blast resistance

Product Range / Production Options Laminated Safety Glass

- Maximum size 9,000mm x 3,300mm
- Thickness range between 4mm - 19mm
- Edge working
- Mitered edges
- Drilled holes
- Countersunk holes
- Corner cut-outs
- Edge cut-outs
- Centre cut-outs
- Round corners
- Shaped glass
- Fully enamelled glass, screen printing

Enamelling

SGT uses enamels to provide toughened glass in a range of different colours. Enamels can be applied onto any smooth-surfaced flat glass that can be toughened. The enamels are rolled onto the surface and then fired onto the glass at temperatures between 600 and 620°C. Please note that due to applying the enamels by rolling, the entire glass sheet will be enamelled.

Screen printing

Company Profile of **Sicherheitsglastechnik Oelsnitz (Vogtl.) GmbH**

A service of glassglobal.com, an affiliate of glassglobal group.

Les informations publiées sur ce document sont soumises au droit d'auteur et appartiennent à la société en question resp. à la source des adresses. Tous les droits sont réservés expressément. N'importe quel utilisateur qui accède à un tel matériel peut faire ainsi seulement pour sa propre utilisation personnelle, et l'usage d'un tel matériel est au risque unique de l'utilisateur. La redistribution ou toute autre exploitation commerciale des adresses est expressément interdite. Là où une adresse est fournie par un tiers, chaque utilisateur accepte d'observer et être lié par les limites spécifiques de l'utilisation. Glass Global ne représente ou n'approuve pas l'exactitude ou la fiabilité d'aucune des informations citées dans les adresses ou pages externes auxquelles l'on se réfère ici. www.glassglobal.com - The International Portal to the Glass Industry - OGIS GmbH